Information for users

PPE CATEGORY II

 \mathbf{EN}

| EN 420:200 | 3+A1:2009 | EN 3 | 388:2016 | | PPE CATEGORY II | | | | | | |
|---|---|---------------------|-----------------------|---------------------|---|--|---|---|----------|--|--|
| | ead the ins | | • | | In accordance with the requirements of the Regulation (EU) 2016/425. blyester/cotton, latex palm and fingertips, crinkle finish | | | | | | |
| Product: Design: | | | 3420 001 157 X | | | | Production design: | | 12001010 | | |
| Material: | 65 % Polyester, 35 % Cotton, Latex coating. | | | | | | | | | | |
| Purpose: The product's basic function is to protect from injuries that could occur in the work spaces for which the product is designed. It also serves as hand protection against soiling and as protection in the working environment while performing work with mechanical hazards. Put the gloves on dry, clean hands. | | | | | | | | | | | |
| The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor) | | | | | | | | | | | |
| A (0-4) | А | brasion resistance: | | Performanc | Performance level 3 | | | The protection works only against the specified | | | |
| B (0-5) | | ut resistance | | Performanc | Performance level2Performance level4 | | പ | hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels | | | |
| C (0-4) | | ear resistance | | Performanc | | | -/ | | | | |
| D (0-4) | | uncture resistance | | Performanc | Performance level 3 | | | | | | |
| E (A-F) | C | ut Resistance (TDM) | | Performanc | Performance level X | | D.E.F. | (classes) are determined based on the tests | | | |
| F(P/X) or n | othing II | mpact protection | | Performanc | Performance level X | | | carried out in accordance with the conditions determined in the valid standards specified here. | | | |
| EN 420 - p | EN 420 - protective gloves (general requirements) | | | | | | | As for the gloves with two or more layers it does | | | |
| (1-5) | Dexterity F | | Performanc | Performance level 5 | | | not necessarily reflect the properties of the out | | | | |
| $,,X^{\prime\prime} = test$ | ,,X'' = test not performed or not applicable | | | | | | | layer. | | | |

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use for manipulating hot or heated objects, toxic chemicals or greasy objects. Gloves material may be damaged by oil, mineral oil, greasy and solvent organic. Not resistant to soaking. It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles.

The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Washing or dry cleaning is not recommended. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: The gloves contain allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

| Marking - exa | ample: | | | |
|---------------|---|---------------|--|--|
| "ROXY" | Type of gloves | | | |
| 7 | Size | | 0400 001 157 07 | |
| EN388 | Pictogram and number of the standard that the product complies with | O ROXY | 3420 001 157 07 ZA/2015/415 | |
| 3243X | Results of the tests carried out | | | |
| CE | Conformity mark | TRXS 0 | 8 591940 167691 > | |
| cat II | Glove category | EN420 EN388 | CZ: 65% polyester, 35% bavina diañ a prsty | |
| Í. | Symbol indicating the necessity to read the instructions | | povrstveny latexem SK: 65% polyester, 35% bavlna dlaň a prsty potlahnuté latexom PL: 65% poliester, 35% bavelna dloni i palce pokryte lateksem | |
| "А" | Production identification | cat II 3243X | EN: 65% polyester, 35% cotton palm | |
| 12001010 | Production design | | and fingers coated with latex | |
| Coxes | Manufacturer identification | | | |

