EN 420+A1:2009

EN 388:2003

PPE CATEGORY II

Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425.

Product: Five-fingered gloves, knitted fabric, nitril coating.

Design:	"RITA"	Code:	3630 020 000 XX	Size:	8, 9, 10	
Material:	HPPE - 65% Glass fiber, 15% Nylon, 15% Elastane (Spandex), 5% Nitrile.					

Purpose: These gloves are suitable for work with sharp object. Mechanical risk: gardening, homework, logistic, construction, manufacturing industry (automobile, glass, aeronautics), transportation. Do not use these gloves where protection is required in cuffs. Designed for manipulating materials in both dry and damp environments. Put the gloves on dry, clean hands. We recommend that you keep this information for future reference.

The gloves were	e test	ed in accordance with EN 388 - me	echanical hazards (The	e hi	igher the number	er, the higher the protection factor)
A (0-4)		Abrasion resistance:	Performance level 4	4		The protection works only against
B (0-5) C (0-4) D (0-4)		Blade cut resistance (coupe test)	Performance level 5	5		hazards. Do not use the gloves as against different hazards and results apply only for the model of the protection levels (classes). T
		Tear resistance	Performance level 4	4		
		Puncture resistance	Performance level 4	4	\smile	
E (A-F)		Cut Resistance (TDM)	Performance level X	K	A.B.C.D.E.F	levels (classes) are determined by
F(P/X) or nothing		Impact protection	Performance level X	K		tests carried out in accordance conditions determined in the val
EN 420 - protec	tive	gloves (general requirements)				specified here. As for the gloves
(1-5)	Dex	terity	Performance level 5			more layers it does not necessari
$,,X'' = test\ not\ per$	rform	properties of the outer layer.				

works only against the specified ot use the gloves as a protection ent hazards and classes. The only for the model classes, not for levels (classes). The protection s) are determined based on the out in accordance with the termined in the valid standards . As for the gloves with two or does not necessarily reflect the

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. To prolong the life of the glove. The gloves are designed for single or short-term use only. Damp gloves should be dried out at a room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush, nitrile Wipe with a damp cloth. Do not clean chemically, bleach, dry in a tumble dryer, or iron. The gloves that are worn through, have holes burned through, or are hard must be replaced. We are not responsible for possible reduction of the protective function caused by improper maintenance. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: The gloves contain allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment: Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France. The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking - examp	le:	,	
"RITA"	Type of gloves		-
8	Size	_	HPPE 65% skleněné vlákno 15% nylon 15% elastan (Spandex) 5%, nitril HPPE 65% sklené vlákno 15% nylon 15%
EN 388	Pictogram and number of the standard that the product complies with	RITA	elastan (Spandex) 5%, nitril HPPE 65% glass fiber 15% nylon 15% elastane (Spandex) 5%, nitril HPPE 65% wtókno szklane 15% nylon 15%
4544	Results of the tests carried out	8	36156510
C€	Conformity mark		(CAS
cat II	Glove category	EN420 EN388	3630 020 000 08 7A/2019/285
<u> </u>	Notice on the necessity to read the instructions for use	CE Cat II 4544	
,,A"	Production identification		
36156510	Production model		8 5 9 1 9 4 0 1 6 2 7 8 8 >
ZA/2019/285	Lot		
(Cxs	Manufacturer identification		

