## EN 420+A1:2009

EN 388:2016

PPE CATEGORY II

Read the instructions carefully.

In accordance with the requirements of the Regulation (EU) 2016/425.

**Product:** Seamless gloves made of thick mixed yarn, latex impregnation.

Design:	"BLANCHE"	Code:	3420 003 102 XX	Size:	9, 10
Material:	65% Polyester, 35% Cotton, coating Latex.				

Purpose: They may serve as a protection of hands against dirt and protection in the working areas where workers have to face mechanical hazards (construction, logistics, storage, agriculture, etc.) for example when handling small loads. Put the gloves on dry, clean hands

The gloves wer	o tost	ted in accordance with EN 388 - me	schanical hazards (The l	higher the numb	per, the higher the protection factor)
The gloves wel	C iesi	1		inglici die numo	
A (0-4)		Abrasion resistance:	Performance level 3		The protection works only against hazards. Do not use the gloves as against different hazards and classes apply only for the model classes,
B (0-5)		Blade cut resistance (coupe test)	Performance level 1	- ( <u>止</u> )	
C (0-4)		Tear resistance	Performance level 4	\ <del>-</del> /	
D (0-4)		Puncture resistance	Performance level 2	$\smile$	protection levels (classes). The pro
E (A-F)		Cut Resistance (TDM)	Performance level X	A.B.C.D.E.F	(classes) are determined based on the out in accordance with the condition in the valid standards specified her
F(P/X) or nothing		Impact protection	Performance level X		
EN 420 - protec	ctive	gloves with two or more layers			
(1-5)	Dex	terity	Performance level 3		necessarily reflect the properties of the protection levels (classes) apply
$,,X''=test\ not\ pe$	erform	gloves not washed or cleaned.			

The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here. As for the gloves with two or more layers it does not necessarily reflect the properties of the outer layer. The protection levels (classes) apply only for new gloves not washed or cleaned.

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. To prolong the life of the glove. The gloves are designed for single or short-term use only. Damp gloves should be dried out at a room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush, nitrile Wipe with a damp cloth. Do not clean chemically, bleach, dry in a tumble dryer, or iron. The gloves that are worn through, have holes burned through, or are hard must be replaced. We are not responsible for possible reduction of the protective function caused by improper maintenance. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: The gloves contain allergen - Latex. They may cause an allergic reaction if used by sensitive people, including anaphylactic shock. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking - example:				
"BLANCHE"	Type of gloves			
9	Size			
EN 388	Pictogram and number of the standard that the product complies with			
3142X	Results of the tests carried out			
C€	Conformity mark			
cat II	Glove category			
(i)	Notice on the necessity to read the instructions for use			
,,A"	Production identification			
ZA/2018/621	Lot			
(Cosi	Manufacturer identification			





