EN 420:2003+A1:2009

EN 388:2016

PPE CATEGORY II

Read the instructions carefully.

Complies with the requirements of the Regulation (EU) 2016/425

Product: Protective gloves against mechanical hazards.							
Design:	"TECHNIK"	Code:	3210 010 251 00	Size:	7–11	Material:	Goat or sheep grain leather, cotton knit
Design:	"TECHNIK A"	Code:	3210 086 401 00	Size:	7-11	Material:	Goat or sheep grain leather, cotton knit
Design:	"TECHNIK PLUS"	Code:	3210 009 801 00	Size:	7-11	Material:	Goat or sheep grain leather, synthetic knit
Design:	"TECHNIK ECO"	Code:	3210 011 801 00	Size:	7-11	Material:	Goat or sheep grain leather, cotton knit
Design:	"TALE"	Code:	3210 012 000 00	Size:	7-11	Material:	Goat or sheep grain leather, cotton knit
Design:	"MIKE"	Code:	3210 014 250 05	Size:	5	Material:	Goat or sheep grain leather, cotton knit

Intended use: It serves as hand protection against pollution and protection in the working environment when working with minor mechanical hazards (abrasion, dirt...), for example: assistant construction works, logistics, light industry, warehouse handling, agriculture. "TECHNIK", "TECHNIK A" and "MIKE" gloves - special purpose gloves with shortened length. They should not be used for normal work - use them only for work where only palm protection is required and wrist protection is not required. Put the gloves on dry, clean hands.

The gloves we	re tes	ted in accordance with EN 388 -	mechanical hazards (The h	igher the numbe	er, the higher the protection factor)	
A (0-4)		Abrasion resistance:	Performance level 2		The protection works only agains	
B (0-5)		Cut resistance	Performance level 1	<u> </u>	hazards. Do not use the gloves a against different hazards and class apply only for the model classe protection levels (classes). The pr (classes) are determined based carried out in accordance with determined in the valid standards	
C (0-4)		Tear resistance	Performance level 1	\ - /		
D (0-4)		Puncture resistance	Performance level 2			
E (A-F)		Cut Resistance (TDM)	Performance level X	A.B.C.D.E.F.		
F(P/X) or nothing		Impact protection	Performance level X]		
EN 420 - prote	ctive	gloves (general requirements)			As for the gloves with two or more	
(1-5)	Dexterity		Performance level 5		not necessarily reflect the properti	
,,X" = test not	perfo	layer.				
					and the second s	

he protection works only against the specified zards. Do not use the gloves as a protection gainst different hazards and classes. The results oply only for the model classes, not for the otection levels (classes). The protection levels lasses) are determined based on the tests arried out in accordance with the conditions etermined in the valid standards specified here. s for the gloves with two or more layers it does ot necessarily reflect the properties of the outer

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking. It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. For dulling during the cut resistance test (B), the coupe test results are only indicative while the TDM cut resistance test (E) is the reference performance result. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. To prolong the life of the glove. The gloves are designed for single or short-term use only. Damp gloves should be dried out at a room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. The gloves that are worn through, have holes burned through, or are hard must be replaced. We are not responsible for possible reduction of the protective function caused by improper maintenance. Under suitable storage conditions, shelf life is 5 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: Materials which come into contact with the user's skin can cause an allergic reaction in sensitive individuals. They may contain trace amounts of chromium in accordance with the exposure limit values. If skin irritation or allergic reaction contact, do not use gloves and seek medical advice.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 1023, INSTITUT PRO TESTOVÁNI A CERTIFIKACI, a. s., T. Bati 299, Louky, 763 02 Zlín, Czech Republic.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking (sample) - description:							
TECHNIK	Type of gloves	Ţį.	Notification on the necessity to read the instructions for use				
10	Size	"HM"	Production identification				
EN388	Pictograms and numbers of standards which the product complies with	(Cos	Manufacturer's identification				
2112X	Design classes	∑ _{XX/XXX}	Use by (month/year)				
C€	Mark of conformity	ZA/XXXX/XXX CAT II	Lot – mark/year/order number PPE category				

