Information for users

EN 420:2003+A1:2009 EN 388:2016+A1:2018 PPE CATEGORY II Read the instructions carefully. In accordance with the requirements of the Regulation (EU) 2016/425									
Product:	Product: Five-fingered gloves, knitted fabric, polyurethane (PU) coating.								
Design:	"CIT	A II"	Code:	3630 002 700 00		Size:		7, 8, 9, 10, 11	
	"CITA 3F"			3630 136 700 00				6,7,8, 9, 10	
Material: 43% UHMWPE/ 22% Polyester/ 15% Nylon/ 11% Glass fibre / 9% Elastane SPANDEX, coating: PU.							g: PU.		
	UHMWPE = ultra-high molecular weight Polyethylene.								
	Purpose: These gloves are suitable for work with sharp object, glass etc. Do not use these gloves where protection is required in cuffs. We								
	recommend that you keep this information for future reference. Put the gloves on dry, clean hands.								
The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor)									
A (0-4)		Abrasion resistance:	Per	formance level 4		_		n works only against the specific	
B (0-5)		Blade cut resistance	Per	formance level X	A.B.C.D.E.F.		hazards. Do not use the gloves as a protection		
C (0-4)		Tear resistance	Per	formance level 4			against different hazards and classes. The results apply only for the model classes, not for the		
D (0-4)		Puncture resistance	Per	formance level 3			protection levels (classes). The protection levels (classes) are determined based on the tests		
E (A-F)		Cut Resistance (TDM	(I) Per	formance level D					
F(P/X) or nothing		Impact protection	Per	Performance level X				in accordance with the conditions in the valid standards specified here.	
EN 420 - protective gloves (general requirements)								i the valid standards specified her oves with two or more layers it do	
(1-5)	Dex	terity	Per	formance level 5				y reflect the properties of the out	
,,X'' = test not performed or not applicable layer.									
									-

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use for manipulating hot or heated objects, toxic chemicals or greasy objects. Gloves material may be damaged by oil, mineral oil, greasy and solvent organic. Not resistant to soaking. It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles.

The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush, PU wipe with a damp cloth. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: Materials which come into contact with the user's skin can cause an allergic reaction in sensitive individuals. Contains traces of DMF in compliance with occupational exposure limits. If skin irritation or allergic reaction do not use gloves and contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking	(sample) -	description:

in an in the second sec							
CITA II	Type of gloves	í.	Symbol indicating the necessity to read the instructions				
10	Size	"А"	Identification production				
EN388	Pictogram and number of the standard that the product complies with	AC CONT	Manufacturer identification				
4X43D	Results of the tests carried out	12/2019	Month and year of production				
CE	Conformity mark	ZA/2019/388 CAT II	Lot - Mark / year / number Glove category				

