

CERVA 01020061

PROTECTIVE GLOVES FOR WELDERS, TYPE B

Description: Five fingers protective gloves for welders made from soft cow leather without lining. Size 8, 10, 11. Each pair is marked by logo of manufacturer, article number, manufacturing date and pictograms of protection in accordance with Regulation (EU) 2016/425, EN 420:2003+A1:2009, EN388:2016 and EN12477+A1:2005. PPE personal protective equipment category II.

User: Gloves are designed for welding works and protection against mechanical risks in dry conditions. The gloves are recommended for welding processes which require higher dexterity, for example a TIG welding.

Features and marking:

read the user manufacturer instruction EU conformity marking
mechanical hazards icon heat hazards icon

1111+ - protection levels EN388:2016

Abrasion resistance: 1 (1-4)

Cut resistance: 1 (1-5)

Tear resistance: 1 (1-4)

Puncture resistance: 1 (1-4)

TDM cut resistance: x - not tested, Test method appears not to be suitable for the glove design/ material dexterity: 4

31xx3x - protection levels EN407:04

Burning behavior class 3 (1-4)

Contact heat class 1 (1-4)

Conductive heat class X (1-4)

Radiant heat class X (1-4)

Small splashes of molten metal class 3 (1-4)

Large quantities of molten metal class X (1-4)

EN12477+A1:05 TYPE B - standard number, year of issue and type of welders gloves

Maintenance and usage of safety gloves: Protect gloves against radiant heat, do not expose to organic solvents and their vapours, lubricants, fats, mineral oils and water. Remove rough dirt with a brush and let gloves dry freely at room temperature after use. Gloves cannot be machine washed or dry cleaned.

Warning: Gloves should not be used if there is a risk of entanglement with moving machinery parts. Protective measures refer only to the protection of the hands. Never use worn through, torn or otherwise damaged gloves. In susceptible individuals, skin irritation may occur in this case do not use the gloves any more. At present there is no standardised test method for detecting the UV penetration through the gloves materials used. Nevertheless, the current methods to manufacture protective welding gloves do normally not allow the UV penetration. As well, arc welding settings up do not allow a welder protection in case of a direct contact with all low voltage parts, the gloves do not provide protection against electric shock caused by faulty equipment or work under electric voltage. If the gloves are wet, soiled or soaked with sweat, the electric resistance is reduced and the risk may increase.

Transport and storage: Gloves should be transported in the original packaging or in a plastic bag. Gloves should be stored in a cool, dry environment away from direct sunlight. Shelf life is 5 years from the date of manufacture in suitable conditions.

Type certificate has been issued by a notified body No. 2369 Vipo a.s., Gen. Svobodu 1069/4, Partizánske, Slovak Republic. The declaration of conformity is available on the www.cerva.com/conformity.htm.

Manufacturer: CERVA GROUP a.s., Prúmyslová 483, 252 61 Jeneč, Czech Republic

AL DOREZA MBROJTESE, LLOJI B

Pérszhkrimi: Dorezat jané tè prodhurra prej lëkure ciliçore tè lëmuar dhe tè ashpér. Jané pa astar. Ofrohen nò madhësinë numr 8, 10, 11. Cdo pôle doreza èshtë e pajisur me logo e produshtit, numri i modelit, viti e prodhimit dhe pikogramen daliusë tè prodhusest ne përpjekje me normën evropiane (EU) 2016/425, EN 420:2003+A1:2009, EN388:2016 dhe EN12477+A1:2005. PMI: Pajisjet mbrojtese personale Kategoria II.

Përvetësimi: Dorezat jané përmendur për mbrojtje e dorës ndaj rezipive të dëmtojnë mekanike që përdorim gjatë pritet si zakonisht sallidni në një mëdësi tè thate. Dorezat jané tè rekomandura për proces që kërkojnë aftësi kajpeje më të lartë, si për shembull gjatë saldimit me TIG.

Karakteristikat dhe kodifikimi:

Piktogram i identifikimi i prodhuesit

symbol i përpshëmrit

piktogram i rrezigjeve Mekanike

piktogram i nxehësisë dhe zjarrit

31xx3x - Shkallat e mbrojtjes EN388: 2016

Resistenza ndaj abrazionit: 1 (1-4)

Resistenza ndaj prejës: 1 (1-5)

Resistenza ndaj carjes: 1 (1-4)

Resistenza ndaj shpimit: 1 (1-4)

Resistenza e prej TDM: x - nuk është testuar. Metoda e testimit duket tè mos jetë e përshtatshme për dijzonin / materialin e fiksuesit

Shkalla e aftësise së kapjes 4

31xx3x - Shkallat e mbrojtjes EN407: 2004

Resistenza ndaj zjarrit.

Resistenza ndaj nxehësisë së transmetuar me kontakt.

Resistenza ndaj nxehësisë së transmetuar me konveksion.

Resistenza ndaj nxehësisë së transmetuar me rezalim.

Resistenza ndaj spikaturjeve të vogla tè metalit.

Resistenza ndaj spikaturjeve të vogla tè metalit.

Resistenza ndaj spikaturjeve tè mëdha tè metalit.

Resistenza ndaj spikaturjeve tè mëdha tè metalit.

Resistenza ndaj zjarrit.

Resistenza ndaj nxehësisë së transmetuar me konveksion.

Resistenza ndaj nxehësisë së transmetuar me rezalim.

Resistenza ndaj spikaturjeve tè vogla tè metalit.

Resistenza ndaj spikaturjeve tè mëdha tè metalit.</

