

INSTRUCTIONS FOR USE


COMPLEX DESIGN

PVC-45G AND PVC-45W APRONS

A. Use

These aprons are designed to protect part of the body against splashes from certain chemicals. They are in conformity and are marked as per requirements of the European Directive 89/686/EEC and its Amendments and they are in compliance with the European Standards EN 340 : 2003 and EN 14605 : 2005.

The aprons are not designed to allow water vapour transmission. As a consequence, for comfort reasons, they should be used for short periods only.

| | | |
|---|--|--|
|  | Chemical permeation performance levels: | Mechanical performance levels: |
| | H ₂ SO ₄ 50% : 6 NaOH 50% : 6 | Abrasion : 6 Flex crack : 6 Trapezoidal tear : 3 Tensile strength : 4 Puncture : 2 Resistance to ignition : 1 |
| Type PB[4] | | |

Warning ! : The information given by the pictograms or through data on chemical resistant breakthrough times is based on lab tests and is therefore advisory only, since it does not necessarily reflect the actual duration in the workplace.

EC-Quality Control for the final product by Centexbel Belgium (I.D. 0493).
 For more detailed information on the apron's performance and to obtain a copy of the Conformity Declaration, please consult Ansell.

B. Precautions for use

1. Before usage, inspect the aprons for any defects or imperfections. If the apron is ripped or punctured during use, dispose of it immediately. If in doubt, do not use the apron, get a new one.

2. It is essential to keep all chemicals from the skin, even if they are thought to be harmless. Therefore, use which are rated with a protection index of 6 or with an excellent degradation rating. In all other cases, the aprons should be used for splash protection or short contact only. For more details regarding chemical suitability, please contact the Ansell technical department.

Ansell Healthcare Europe N.V.

Riverside Business Park, Spey House Boulevard International 55 B-1070 Brussels, Belgium
 Tel. +32 (0) 2 528 74 00 Fax +32 (0) 2 528 74 01 Fax Customer Service +32 (0) 2 528 74 03
<http://www.anselleurope.com> E-mail info@eu.ansell.com



ISO 9001 Certificate
 Number FM 40130

4. Ensure the chemicals cannot enter via the sides of the chest piece.
5. The aprons are not intended for protection against mechanical risks. Mechanical resistance can be assessed from the test results in A.
6. The aprons should not be used for protection against serrated blades or when there is a risk of entanglement with moving machine parts.
7. The aprons do not protect against thermal risks. Do not use with temperatures exceeding 100 °C.

C. Hazardous ingredients

None. For more information, please contact Ansell's Customer service department.

D. Care instructions

Fitting: To put the apron on: slip on the neck loop, then knot the ties in the back.

Storage : Keep out from direct sunlight; store in a cool and dry place.
Keep out from sources of ozone or ignition.

Cleaning : The aprons are not designed to be laundered. Do not reuse.



E. Disposal

Used aprons may be contaminated with infectious or other hazardous materials. Dispose of according to Local Authority Regulations. Landfill or incinerate under controlled conditions.

Ansell Healthcare Europe
Internationale Laan 55
1070 Brussels
Belgium

| Material | Colour | Style | Reference | Dimensions | Thickness |
|-----------------|--------|-------------------------------|-----------|---|-----------|
| PVC unsupported | White | Nylon prelaced grommets | PVC-45W | 70 -111 cm waist girth 180 ±22 cm length | 0.508 mm |
| | Green | | PVC-45G | | |

This apron is available in one size only.

Ansell Healthcare Europe N.V.

Riverside Business Park, Spey House Boulevard International 55 B-1070 Brussels, Belgium
Tel. +32 (0) 2 528 74 00 Fax +32 (0) 2 528 74 01 Fax Customer Service +32 (0) 2 528 74 03
<http://www.anselleurope.com> E-mail info@eu.ansell.com



ISO 9001 Certificate
Number FM 40130